



OPERATING PRESSURE : 10 BARG.
 DISIN PRESSURE : 16 BARG.
 TEST PRESSURE : 21 BARG.

FIRST LAYER ZINC RICH EPOXY AVERAGE 40 Mic
 INTERMEDIATE LAYER EPOXY AVERAGE 40 Mic
 TOP COAT EPOXY AVERAGE 40 Mic (RAL 3020)

ITEM	DESCRIPTION	MATERIAL
1	1" SAFETY VALVE	BRASS
2	HAND PUMP	CAST IRON
3	FOAM TANK 500 LITRES	C.STEEL
4	4" FOAM PROPORTIONER	BRONZE
5	FIRE WATER INLET 2" ANSI B16.5, #150 R.F	C.STEEL
6	FIRE WATER OUTLET 2" ANSI B16.5, #150 R.F	C.STEEL
7	2" CHECK VALVE	D.CAST IRON
8	2" STRAINER	D.CAST IRON
9	2" CHECK VALVE	BRASS
10	DELUGE VALVE (ELECTRICAL ACTUATED)	D.CAST IRON
11	SOLENOID VALVE	

NOTE: FOAM BLADDER TANK 1700 LITER

Date	Design	Drawn	Checked	REV.
Part Name: TOTAL		Drawing No: BT2-02		
Material: AS ASIDE CHART		PROJECT:		



TOL: DIN-7168m
 Size: A4
 Scale:
 Sheet: 1 Of 1
 QTY.: 1